



Description: **LOW TEMP USDA REINFORCED**

**PRODUCT SPECIFICATIONS**  
*SAVE-T PVC STRIP & SHEET*

<b>Roll Size</b>		
THICKNESS:	.040" to .250"	
WIDTH:	4" to 60"	
<b>Material Description</b>		
FINISH:	Double Polished	
COLOR:	Clear	
REINFORCEMENT:	Nylon Beacon - 210 denier	
<b>Physical Properties</b>		
Property	Result	ASTM
Hardness (15 sec. delay)	70 A Scale	D2240
Tensile Strength:	2200 PSI	D412
Ultimate Elongation:	400%	D412
Graves Tear:	220 PPI	D1004
100% Modulus:	1000 PSI	D412
Stiffness: (-20°F)	-	-
Brittleness Temp:	-55° F	D746
Operating Temp:	-30° F to 150° F	-
Specific Gravity:	1.20	D792
Density:	75 lbs. cu.ft.	C-177
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
UV Resistance:	YES	
Flammability Rating:	Select Material Compliant with CA State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warranties of any kind are made as to its accuracy or suitability for particular applications.

**TMI, LLC**  
5350 Campbells Run Road  
Pittsburgh, PA 15205-9738  
Web-Site: [www.tmi-pvc.com](http://www.tmi-pvc.com)

Toll Free: 800-888-9750  
Phone: 412-787-9750  
Fax: 412-787-3665  
E-mail: [customer-service@tmi-pvc.com](mailto:customer-service@tmi-pvc.com)