



## Description: STANDARD PVC

## **PRODUCT SPECIFICATIONS**

SAVE-T PVC STRIP & SHEET

Roll Size		
THICKNESS:	.040" to .250"	
WIDTH:	4" to 60"	
Material Description		
FINISH:	Double Polished	
COLOR:	Clear	
Physical Properties		
Property	Result	ASTM
Hardness (15 sec. delay)	79 A Scale	D2240
Tensile Strength:	2400 PSI	D412
<b>Ultimate Elongation:</b>	350%	D412
Graves Tear:	440	D1004
100% Modulus:	1400 PSI	D412
Stiffness: (-20°F)	44,000 PSI	-
Brittleness Temp:	-33° F	D746
<b>Operating Temp:</b>	0° F to 150° F	-
Specific Gravity:	1.21	D792
Density:	75 lbs. cu.ft.	C-177
Thermal Conductivity (K):	.73	C-177
Thermal Resistance (R):	1.37	C-177
Water Absorption:		
UV Resistance:	YES	
Flammability Rating:	Select Material Compliant with CA State Fire Marshal	
Shipped in a box on 6" cores		

Note: The information contained herein is believed to be reliable but no representations, guarantees or warrantees of any kind are made as to its accuracy or suitability for particular applications.

## **TMI, LLC** 5350 Campbells Run

5350 Campbells Run Road Pittsburgh, PA 15205-9738 Web-Site: www.tmivinylsolutions.com 
 Toll Free:
 800-888-9750

 Phone:
 412-787-9750

 Fax:
 412-787-3665

 E-mail:
 vinylsolutions@tmi-pvc.com