

PRODUCT SPECIFICATIONS

产品技术指标

管材产品规格范围

Range of specifications of tubing products

铜管外径 (英寸) Outer diameter of copper tube(in.)	无缝管外径 (毫米) Outer diameter of seamless tube(mm)	镀锌管公称 DN Nominal diameter of galvanized tube	美乐斯橡塑内 径(毫米) Inner diameter of Mlex rubber(mm)	9mm 厚 (1.8m/ 根) 9mm thickness (1.8m/piece)			15mm 厚 (2m/ 根) 15mm thickness (2m/piece)		20mm 厚 (2m/ 根) 20mm thickness (2m/piece)		25mm 厚 (2m/ 根) 25mm thickness (2m/piece)		30mm 厚 (2m/ 根) 30mm thickness (2m/piece)	
				规格 Size (mm×mm)	根 / 件 piece/ bag	根 / 箱 piece/ carton	规格 Size (mm×mm)	根 / 件 piece/ bag	规格 Size (mm×mm)	根 / 件 piece/ bag	规格 Size (mm×mm)	根 / 件 piece/ bag	规格 Size (mm×mm)	根 / 件 piece/ bag
1/4			6	6×9	180	180								
3/8		6	10	10×9	140	140	10×15	80	10×20	70				
1/2			13	13×9	120	100	13×15	80	13×20	50				
5/8	14	8	16	16×9	100	95	16×15	60	16×20	50				
3/4			19	19×9	100	80	19×15	60	19×20	40				
7/8	22	15	22	22×9	100	70	22×15	60	22×20	40	22×25	30	22×30	25
1	25		25	25×9	80	55	25×15	60	25×20	30	25×25	25	25×30	25
1 1/8	28	20	28	28×9	60	50	28×15	50	28×20	30	28×25	25	28×30	20
1 1/4	32		32	32×9	60	45								
1 1/4	32		34				34×15	40	34×20	30	34×25	25	34×30	20
1 3/8		25	35	35×9	60	40								
1 1/2				38×9	50	30								
1 5/8		25	42	42×9	50	30								
1 5/8		32	43	43×9	50	30	43×15	30	43×20	25	43×25	20	43×30	15
1 7/8		40	48	48×9	50	28	48×15	30	48×20	25	48×25	20	48×30	15
2 1/8			54	54×9	50	25								
2 3/8		50	60	60×9	50	20	60×15	30	60×20	20	60×25	15	60×30	15
	76	70	76				76×15	25	76×20	15	76×25	15	76×30	10
	89	80	89						89×20	15	89×25	15	89×30	10
	108		108						108×20	15	108×25	10	108×30	10

板材 (1.5 米宽)

Planking (1.5m width)

厚度 Thickness	10mm	15mm	20mm	25mm	30mm
米 / 件 m/piece	16m	16m	8m	8m	8m

注：1. 以上规格均为常用规格，如需特殊规格可根据用户要求制作。

2. 板材，管材为浅灰色，需要特殊颜色可根据用户要求制作。

3. 管道外径超过 89mm 建议使用板材。

4. 保温材料需要厚度超过 25mm，采用多层重叠包装，直至所需厚度。

5. 板材宽度可根据用户要求定做 1-2 米。

Notes : 1. The above specifications are those in common use;special specifications are available at customers' request.

2. Planking and tubing are normally in gray. Other colors are available at customers' request.

3. It is recommended to use planking where outer diameter of tubing exceeds 89mm.

4. Multilayer packing is recommended where the thickness of heat insulation materials needs to be greater than 25mm.

5. The width of the planking are available at customers' request for a scope of 1m to 2m.